

S1G300-CA19-14

EC axial fan

sickled blades (S series)

ESM guard grille

ASIA PACIFIC SHENGRUI LIMITED

Phone +00852 56261528

info@apacfan.com

www.apacfan.com

Nominal data

Type	S1G300-CA19-14		
Motor	M1G055-BI		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz		50/60
Type of data definition			ml/cu
Speed	min ⁻¹	900	1250
Power input	W	-	35
Current draw	A		0.27
Max. back pressure	Pa		40
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan

sickled blades (S series)

ESM guard grille

Technical features

Mass	1.4 kg
Size	300 mm
Material of blades	PA plastic
Material of guard grille	Plastic, epylen GT50
Number of blades	5
Direction of rotation	"A"
Type of protection	IP 54
Insulation class	"B"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Speed selection max/min - Soft start - Over-temperature protected motor
Speed steps	2
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Lateral
Protection class	II
Product conforming to standard	CE
Approval	UL 2111; CCC; CSA C22.2 Nr.77





S1G300-CA19-14

EC axial fan

sickled blades (S series)

ESM guard grille

Product drawing



1	Direction of air flow "A"
2	PIN S, speed selection (flat plug 2.8x0.5)
3	PIN L1, phase (flat plug 2.8x0.5)
4	PIN N, neutral conductor (flat plug 2.8x0.5)

EC axial fan

sickled blades (S series)
ESM guard grille


Connection screen

Customer circuit

Connection

Fan / motor

Notes on 2 different speed settings and their applications




EC axial fan

sickled blades (S series)

ESM guard grille

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Stage	U	f	n	P _{ed}	I	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa
1	2	230	50	1250	27	0.21	1220	0
2	2	230	50	1250	30	0.23	1095	15
3	2	230	50	1250	32	0.24	1000	25
4	2	230	50	1250	35	0.27	870	35
5	1	230	50	900	13	0.12	865	0
6	1	230	50	900	14	0.13	780	8
7	1	230	50	900	16	0.15	715	13
8	1	230	50	900	17	0.16	625	18

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

